

Prior Transynth 75W-90

Description	Universal, high-performance, full-synthetic gear oil based on high quality synthetic base oils and special EP-additives.	
Application	Designed for use in automotive manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is a universal product and widely usable. Due to its high thermal stability it is excellent for use in applications with higher operating temperatures.	
Performance Level	Meets the requirements of: API GL-3/GL-4/GL-5/MT-1 Mil-L-2105A/B/C/D/E, Mil-PRF-2105E MB-Approval 235.8, MAN 341 Typ Z2/E3, 342 Typ M3 ZF TE-ML 02B/05B/07A/12B/16F/17B/19C/21B DAF MAN 3343 Typ S Scania STO 1:0 Volvo 97312 Ford M2C200-B/C Mack GO-J	
Typicals	Density at 15 °C, kg/l	0,868
	Viscosity 40 °C, mm ² /s	101,00
	Viscosity 100 °C, mm ² /s	15,40
	Viscosity Index	161
	Flash Point COC, °C	202
	Pour Point, °C	-50
	Total Base Number, mgKOH/g	2,1



Prior-oil is a registered trademark of Eurotex Group Ltd. Produced: Zwijndrecht, Holland by Socaz by order of Eurotex Group Ltd.

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.