



Prior Power Turbo Diesel 15W-40

Description	Mineral 15W-40, heavy-duty diesel engine oil, designed for a wide range of heavy-duty applications as found in trucking and construction industries.	
Application	Multifunctional motor oil formulated for heavy duty service in engines specially designed for on-highway conditions as well as being suitable for a wide range of heavy duty off-highway application. This motor oil is suitable for application in mixed fleets.	
Performance Level	Meets the requirements of: API CH-4/SJ ACEA A3/B3, E2 MB 228.1 MAN 271 VOLVO VDS Mack EO-M Plus Cummins CES 20071/20076 Cat ECF-1-a MTU Type 1 VW 505.00	
Typicals	Density at 15 °C, kg/l	0,863
	Viscosity -20 °C, mPa.s	6220
	Viscosity 40 °C, mm ² /s	86,70
	Viscosity 100 °C, mm ² /s	13,00
	Viscosity Index	150
	Flash Point COC, °C	220
	Pour Point, °C	-42
	Total Base Number, mgKOH/g	10,0
	Sulphate Ash, %	1,22

Prior-oil is a registered trademark of Eurotex Group Ltd. Produced: Zwijndrecht, Holland by Socaz by order of Eurotex Group Ltd.

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.