

Prior Transoil 80W-90

Description	Mineral, solvent refined, multi-grade gear oil with extreme pressure additives for mechanical gears.	
Application	Designed for use in heavy duty vehicle transmissions, especially axle drives with hypoid gears. Not suitable or limited slip differentials.	
Performance Level	Meets the requirements of: API GL-5 Mil-L-2105D ZF TE-ML16B/17B/19B/21A MAN 342 Typ M1	
Typicals	Density at 15 °C, kg/l	0,896
	Viscosity 40 °C, mm ² /s	149,00
	Viscosity 100 °C, mm ² /s	14,80
	Viscosity Index	98
	Flash Point COC, °C	230
	Pour Point, °C	-30
	Total Base Number, mgKOH/g	1,60
	Sulphate Ash, %	0,05



Prior-oil is a registered trademark of Eurotex Group Ltd. Produced: Zwijndrecht, Holland by Socaz by order of Eurotex Group Ltd.

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefullness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.